



UNIVERSITATEA BABEŞ-BOLYAI

FACULTATEA DE MATEMATICĂ ȘI INFORMATICĂ




Bachelor Degree Exam, June 2016 Computer Science - English

Subject 1

Write a program in one of the programming languages Python, C++, Java, C# that:

- (a) **Defines the classes** Student and StudentWithScholarship according to the following UML class diagram:



- The name and city must be not null and non empty, and the scholarship must be greater than zero. The constructors must enforce the constraints.
 - The `toString()` method from the class `Student` returns the name concatenated with the city of the student, while the method `toString()` from class `StudentWithScholarship` appends the scholarship to the string containing the name and the city.
- (b) **Defines a function** that inserts an object of type `Student` into a list of students ordered ascending by name, such that the list remains ordered.
- (c) **Defines a function** that prints a list of students.
- (d) **Defines a function** that has as parameter a list of students, and prints for each city the list of students with scholarship (ordered by name) from that city. Each city is printed only once, in any order.
- (e) The **main function** of the program calls the function indicated at (b) to build a list of four students, from two cities “Arad” and “Oradea”, three of them having scholarships. Then it prints the list of students using the function defined at (c). Finally, it calls the function defined at (d).
- (f) For the data types used in the program, write the specifications of the used operations.

Remarks

- **Do not use sorted containers and sorting operations.**
- **Do not define other methods than those required in the subject.**

You can use existing libraries for data structures (Python, C++, Java, C#).

Subject 2

a. Create a relational database with all the tables in 3NF that will store the following information for an online booking system:

tourists: name, email, city code, city name, country code, country name;

accommodation establishments: name, city code, city name, country code, country name, accommodation type code, accommodation type name (examples of values: pension, hostel, hotel, etc), number of stars, rating, price / night, and a list of **bookings**, for each such booking knowing the tourist, starting date and number of nights.

Prove that the created database is in 3NF, by identifying the functional dependencies.

- b.** For the database created for **a**, solve, using the relational algebra or SQL, the following queries:
- The tourists (name and email) that booked at least a pension whose rating is greater than 9, but didn't book any 3 star hotel with a rating less than 9.
 - The total number of bookings for all the tourists from Cluj in a 5 star hotel in Paris in 2015.
 - The accommodation establishment (name, city name, accommodation type name, number of stars) that has the greatest number of bookings over the last 5 years.

Subject 3

- 3.1** The file **grep.c** contains the code fragment below and is compiled in the user's home directory under the name **grep**. Answer the following questions considering that all instructions are executed successfully.

<pre> 1 int main(int c, char** v) { 2 int p[2], n; 3 char s[10] = "something"; 4 pipe(p); 5 n = fork(); 6 if(n == 0) { 7 close(p[0]); 8 printf("before\n"); 9 if(c > 2) 10 execvp("grep","grep",v[1],v[2],NULL); 11 strcpy(s, "after"); 12 write(p[1], s, 6); 13 close(p[1]); 14 exit(0); 15 } 16 close(p[1]); 17 read(p[0], s, 6); 18 close(p[0]); 19 printf("%s\n", s); 20 return 0; 21 }</pre>	<p>a) Enumerate and explain the possible values of variable n.</p> <p>b) What will display the following executions on the screen, considering that the user's home directory does not appear in the PATH environment variable?</p> <ul style="list-style-type: none"> b.1) grep grep grep.c b.2) ./grep grep grep.c b.3) ./grep grep
---	---

- 3.2** File **abc.sh** contains the UNIX Shell script below. Answer the following questions.

<pre> 1 n=0 2 for i in `cat \$1`; do 3 c=`echo \$i cut -c1` 4 if echo \$i grep -q "^[0-9][0-9]*\$"; then 5 echo \$i >> \$1.nr 6 elif echo \$c grep -q "[A-Za-z]"; then 7 echo \$i >> \$c 8 else 9 n=`expr \$n + 1` 10 fi 11 done 12 echo \$n</pre>	<p>a) Explain the regular expression on line 4</p> <p>b) What will happen if the script is executed without arguments?</p> <p>c) What will print the execution <code>./abc.sh f3</code> on the screen and what files (name and content) will it create, if <code>f3</code> contains “abc 74 2-8 aa 3a =c b2” and the execution is done in a directory containing only the files <code>abc.sh</code> and <code>f3</code>?</p> <p>d) Give an example of file <code>f3</code> so that the execution at the point above creates 4 new files, none of which has the prefix <code>f3</code> in their name.</p>
---	--

Remarks: All subjects are compulsory. Each subject will be graded with a mark between 1 and 10 by both evaluators.

Time limit: 3 hours

BAREM

INFORMATICĂ

Subiect 1 (Algoritmică și Programare):

Oficiu – 1p

Definirea clasei Student – **0.75p** din care

 attribute – 0.25

 constructor – 0.25

 metode - 0.25

Definirea clasei StudentBursier – **1.25p** din care

 relația de moștenire – 0.25

 constructor – 0.5

 metoda `toString()` – 0.5

Funcția de la punctul b) – **2p** din care

 signatura corectă - 0.1p

 algoritmul de inserare în interiorul listei - 1.8p

 – parcurgere listă și determinarea poziției de inserare – 1.6p

 – adăugare element pe poziția determinată anterior – 0.2

 returnare rezultat - 0.1p

Funcția de la punctul c) - **0.5p** din care

 signatura corectă - 0.1p

 parcurgere listă și afișare – 0.4p

Funcția de la punctul d) – **2.5p** din care

 determinare lista bursieri din orașe – 2p

 tipărire perechi – 0.5p

Funcția de la punctul e) – **0.5p**

Specificațiile operațiilor tipurilor de dată folosite – **1.5p**

Subiect 2 (Baze de date)

1 punct oficiu

Problema a:

1 punct pentru dependențe funcționale

2 punct pentru tabelele în 3NF;

1 punct pentru justificare.

Problema b:

1 puncte pentru b1

1.5 puncte pentru b2

2.5 puncte pentru b3

Subiect 3 (Sisteme de operare):

Oficiu: 1p

3.1

a) 1p - Valorile posibile

 1p - Explicații

b.1) 1p - Afisează linia 10

b.2) 1p - Afisează "înainte", linia 10 și "ceva"

b.3) 1p - Afisează "înainte" și "după"

3.2

a) 1p - Secvență una sau mai multe cifre

b) 0.5p - Comanda "cat" așteaptă input de la intrarea standard

- c) 0.5p - Afisează 3 pe ecran
 - 0.5p - Fișierul f3.nr conținând 74
 - 0.5p - Fișierele dicționar a și b, conținând "abc aa" respectiv "b2"
- d) 1p - Orice secvență de cuvinte dintre care 4 încep cu litere diferite